

(12) United States Patent

Fuerst et al.

(54) SENSOR DEVICE FOR DETECTING AN ANALYTE

(71) Applicant: Roche Diabetes Care, Inc.,

Indianapolis, IN (US)

Inventors: Otto Fuerst, Viernheim (DE);

Johannes Pill, Leimen (DE); Bernd

Roesicke, Mannheim (DE)

Assignee: ROCHE DIABETES CARE, INC.,

Indianapolis, IN (US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 640 days.

(21) Appl. No.: 14/087,347

(22)Filed: Nov. 22, 2013

Prior Publication Data (65)

> US 2014/0083872 A1 Mar. 27, 2014

Related U.S. Application Data

(63) Continuation of application No. PCT/EP2012/059593, filed on May 23, 2012.

(30)Foreign Application Priority Data

May 23, 2011 (EP) 11167141

(51) Int. Cl.

G01N 27/327 (2006.01)

G01N 27/403 (2006.01)

(Continued)

(52) U.S. Cl.

CPC G01N 27/3271 (2013.01); A61B 5/14532 (2013.01); A61B 5/14546 (2013.01);

(Continued)

US 9,910,007 B2 (10) Patent No.:

(45) Date of Patent:

Mar. 6, 2018

Field of Classification Search (58)

CPC G01N 27/414; G01N 27/3275; G01N 27/3276; G01N 27/403; G01N 27/404

See application file for complete search history.

(56)References Cited

U.S. PATENT DOCUMENTS

4,324,256 A 4/1982 Vesterager 4,659,434 A 4/1987 Driscoll et al.

(Continued)

FOREIGN PATENT DOCUMENTS

2228004 A1 9/2010 EP WO 9701091 A1 1/1997

(Continued)

OTHER PUBLICATIONS

Sensors 2008, 8, 1400-1458.*

(Continued)

Primary Examiner — Alexander S Noguerola (74) Attorney, Agent, or Firm — Bose McKinney & Evans LLP

ABSTRACT (57)

A sensor device for detecting at least one analyte in a fluid, in particular in a body fluid, is disclosed. The sensor device includes at least one closed detector chamber and at least one electrical sensor having at least one sensor electrode. The detector chamber can be connected to the fluid in such a way that the analyte can penetrate into the detector chamber. The detector chamber includes at least one detector substance. The detector substance is designed to influence at least one electrical property of the electrical sensor, in particular at least one electrical property of the sensor electrode, depending on a concentration of the analyte in the detector chamber.

23 Claims, 6 Drawing Sheets

